

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1. (original) An apparatus for performing acoustic investigation of a subterranean formation having a wellbore therethrough, comprising:
 - a transmitter configured to transmit acoustic signals;
 - a receiver configured to receive acoustic signals; and
 - an acoustic attenuation section disposed between said transmitter and said receiver and comprising one or more springs connected in series, each spring being disposed within a housing so that the housing limits the deflection of the spring under an axial load.
2. (previously presented) An apparatus for performing acoustic investigation of a subterranean formation having a wellbore therethrough, comprising:
 - a transmitter configured to transmit acoustic signals;
 - a receiver configured to receive acoustic signals; and
 - an acoustic attenuation section disposed between said transmitter and said receiver and comprising one or more springs connected in series, each spring being disposed within a housing so that the housing limits the deflection of the spring under an axial load, wherein said acoustic attenuation section further comprises a plurality of nodal masses disposed along said attenuation section.
3. (previously presented) The apparatus of claim 2 wherein said nodal masses aid in attenuation of low frequency signals and resist compression loads on the attenuation section.
4. (original) The apparatus of claim 1 wherein said springs are helical springs coated with a layer of resilient material.

5. (original) The apparatus of claim 1 wherein said springs have a stiffness of at least 10,000 pounds per inch of deflection.
6. (original) The apparatus of claim 1 wherein said springs have a stiffness of at less than 30,000 pounds per inch of deflection.
7. (original) The apparatus of claim 1 wherein the coils of said springs have radial holes extending therethrough.
8. (original) The apparatus of claim 1 wherein the outer surface of the spring is separated from the inner surface of the adjoining housing by at least 0.010 inches.
9. (original) The apparatus of claim 1 wherein the outer surface of the spring is separated from the inner surface of the adjoining housing by less than 0.100 inches.
10. (original) The apparatus of claim 1 wherein the outer surface of the housing is covered with an attenuating material.
11. (original) The apparatus of claim 1 further comprising one or more rod members adapted to interconnect between two springs.
12. (previously presented) An apparatus for performing acoustic investigation of a subterranean formation having a wellbore therethrough, comprising:
 - a transmitter configured to transmit acoustic signals;
 - a receiver configured to receive acoustic signals;
 - an acoustic attenuation section disposed between said transmitter and said receiver and comprising one or more springs connected in series, each spring being disposed within a housing so that the housing limits the deflection of the spring under an axial load, and

wherein said acoustic attenuation section further comprises a plurality of nodal masses disposed along said attenuation section; and

one or more rod members adapted to interconnect between two springs, wherein said nodal masses are disposed about said rod members.

13. (previously presented) The apparatus of claim 12 further including a layer of resilient material disposed between at least one of said rod members and at least one of said nodal masses.

14. (original) The apparatus of claim 1 wherein said attenuation section is capable of axial loads of 100,000 pounds.

15. (original) The apparatus of claim 1 wherein said attenuation section is filled with fluid.

16. (cancelled)

17. (previously presented) An apparatus for attenuation of an acoustic signal comprising;
a plurality of springs connected in series to form an elongated body;
a plurality of housings corresponding in number to and disposed about said springs;
wherein said housing limits the axial deflection of said springs; and
a plurality of nodal masses corresponding in number to said springs and disposed along the length of the body.

18. (currently amended) The apparatus of claim [[16]] 17 further comprising a plurality of rod members, wherein each rod member is axially interconnected between two of said plurality of springs.

19. (previously presented) An apparatus for attenuation of an acoustic signal comprising;
a plurality of springs connected in series to form an elongated body;

a plurality of housings corresponding in number to and disposed about said springs;
wherein said housing limits the axial deflection of said springs; and

a plurality of masses and a plurality of rod members, wherein said rod members are axially disposed between and connected to adjacent springs and said masses are positioned about said rod members.

20. (currently amended) The apparatus of claim [[16]] 19 wherein said masses are separated from said rod members by a layer of attenuating material.

21. (currently amended) The apparatus of claim [[16]] 19 wherein said springs are coated with a layer of resilient material.

22. (currently amended) An apparatus for attenuation of an acoustic signal comprising:
a plurality of springs connected in series to form an elongated body; and
a plurality of housings corresponding in number to and disposed about said springs;
wherein said housing limits the axial deflection of said springs. ~~The apparatus of claim 16~~
wherein said springs are helical springs with a minimum stiffness of 10,000 lbs/in.

23. (currently amended) The apparatus of claim [[16]] 19 wherein a circumferential gap of between 0.010 and 0.100 inches is maintained between the outside surface of said spring and the inside surface of said housing.

24. (currently amended) The apparatus of claim [[16]] 19 wherein the outside surface of said housings are coated with an attenuating material.

25. (original) A method for attenuating acoustic energy transmitted along an acoustic tool, wherein the acoustic tool comprises a transmitter section, a receiver section, and an attenuation section disposed between the transmitter and receiver sections, comprising:

transmitting acoustic energy from the transmitter section into the attenuation section;

transmitting acoustic energy through the attenuation section to produce an attenuated acoustic energy, wherein the attenuation section comprises a one or more springs connected in series, a corresponding number of housings disposed about the springs, and a corresponding number of nodal masses; and

receiving the attenuated acoustic energy at the receiver.

26. (original) A method for transmitting acoustic energy along an acoustic tool, wherein the acoustic tool comprises a transmitter section, a receiver section, and an attenuation section disposed between the transmitter and receiver sections, comprising:

receiving acoustic energy from the transmitter with a first spring, wherein the first spring is enclosed within a housing that prevents extension of the spring beyond a predetermined limit;

receiving acoustic energy from the first spring with a connecting rod; wherein the connecting rod possesses a nodal mass that prevents compression of the spring beyond a predetermined limit;

receiving acoustic energy from the connecting rod with a second spring; and

receiving acoustic energy with the receiver via the second spring, wherein the acoustic energy received via the second spring is attenuated relative to the acoustic energy received by the first spring for all frequencies greater than 500 Hz.